

Pool Fittings

ABS Inlets

Floor Inlet ABS Slip Fit

Made in white ABS with Ø63 mm outer connection and Ø50mm inner wall and screws in stainless steel. Its unique design permits 360° dispersion of fresh water in the pool. Max. Recommended flow rate: 12m³/h, flow rate can be manually regulated with the help of an adjustable screw fitted on top centre of the inlet.



Code	Description	Std packing	Volume (m³)
01592825	Floor Inlet ABS Slip Fit	24	0.020

Floor Inlet ABS threaded

Made in white ABS with 2" outer connection thread and Ø50 mm inner wall. Max. recommended flow rate: 12m³/h. Its unique design permits 360° dispersion of fresh water in the pool.



Code	Description	Std packing	Volume (m³)
01592825-2	Floor Inlet ABS Threaded	24	0.020

Floor Inlet ABS threaded for Liner

Made in white ABS with 2" outer connection thread and Ø50 mm inner wall. Supplied with gaskets, flanges and screws for Liner fixing. Max. Recommended flow rate: 12m³/h, flow rate can be manually regulated with the help of an adjustable screw fitted on top centre of the inlet.



Code	Description	Std packing (m³)	Volume (m³)
01592825-1	Floor Inlet ABS Threaded for Liner	12	0.020

Wall Return Inlet ABS Slip Fit

Made in white ABS with Ø50 mm outer connection. Max recommended flow rate: 9m³/h.



Code	Description	Std packing (m³)	Volume (m³)
01592829	Wall Return Inlet ABS Slip Fit	12	0.020



NEW LINE

ATECPOOL HIGH QUALITY Stainless Steel AISI 316

Find everything you would ever need for an adequate water circulation in your swimming pool.

