

# Pool Fittings

## SS Inlets

### Return Inlet AISI 316

Direction-adjustable return inlet in polished stainless steel AISI 316 with outer thread 1½" and Ø20 mm eyeball.

Recommended flow: 4.5 m³/hr.



Code	Description	Length (mm)	Weight (kg)	Volume (m³)
01592858	Return Inlet AISI 316	50	0.30	0.001

### Floor Inlet AISI 316

Adjustable floor return inlet made of polished stainless steel AISI 316 with 2" external thread. Max. Recommended flow rate: 14m³/h, however, flow rate can be manually regulated with the help of an adjustable screw.



Code	Description	Length (mm)	Weight (kg)	Volume (m³)
01592862	Floor Inlet AISI 316	50	0.90	0.002

### Adjustable Return Inlet AISI 316

Adjustable Return Inlet in AISI 316. Flow rate can be manually regulated with the help of an adjustable screw. Available in two female threaded connections. Maximum flow rate for 2" female threaded 21.5m³/hr. Maximum flow rate for 3" female threaded 40 m³/hr.



Code	Description	Flow rate (m³/h)	Weight (kg)	Volume (m³)
01592859	Adjustable Return Inlet 2"	21.5	0.7	0.002
01592861	Adjustable Return Inlet 3"	40	1.1	0.003

### Adjustable Floor Return Inlet

Adjustable Floor Return Inlet in chromed brass. Flow rate can be manually regulated with the help of an adjustable screw located underneath the front cover. Available in two male threaded connections. Maximum flow rate for 2" male threaded 22 m³/hr. Maximum flow rate for 3" male threaded 42 m³/hr.



Code	Description	Flow rate (m³/h)	Weight (kg)	Volume (m³)
01592859-1	Adjustable Floor Inlet 2"	22	0.7	0.002
01592861-1	Adjustable Floor Inlet 3"	42	1.1	0.003

### Suction Inlet AISI 316

Suction inlet in polished stainless steel AISI 316 with outer thread 1 1/2". Length 50 mm, supplied with cover.



Code	Description	Length (mm)	Weight (kg)	Volume (m³)
01592860	Suction Inlet AISI 316	50	0.30	0.001

### Suction Inlet with threaded cover AISI 316

Suction inlet in polished stainless steel AISI 316 with outer thread 2". Length 40 mm, supplied with threaded cover.



Code	Description	Length (mm)	Weight (kg)	Volume (m³)
01592860-1	Suction Inlet threaded cover AISI 316	40	0.30	0.001