

# Spa Fittings Accessories

## Adjustable Jet Ø50x50

Made of white ABS for perfect gluing to PVC pipes. Ø50mm water inlet and air inlet. Flow – 4.5 m<sup>3</sup>/hr. Unique design permits for a combination of air and water massage by way of a venture system. Atmospheric Pressure at 0.8 bar. Available with stainless steel AISI 316 trim.



Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590050	JET 50X50 ABS	6.92	0.027	25
00590057	JET 50X50 ABS with S.S. Trim	9.92	0.028	25

## Adjustable Jet Ø 1.5"x1.5"

Made of White ABS for perfect gluing to PVC pipes. Ø1.5" water inlet and air inlet. Flow – 4 m<sup>3</sup>/hr. Unique design permits for a combination of air and water massage by way of a venture system. Atmospheric Pressure at 0.8 bar. Available with stainless steel AISI 316 trim.



Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590055	JET 1.5"x1.5" ABS	5.82	0.026	25
00590059	JET 1.5"x1.5" ABS with S.S. Trim	9.02	0.028	25

## Adjustable Jet Ø 1"x 1" Chrome

Made of White ABS with Chrome front finish for perfect gluing to PVC pipes . Ø1" water inlet and air inlet. Flow – 2.2m<sup>3</sup>/hr. Unique design permits for a combination of air and water massage by way of a venture system, atmospheric pressure at 0.8 bar.



Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590060	JET 1" X 1" ABS with Chrome front	6.92	0.028	12

## SPA Main Drain 2"

Made of White PVC with adaptor union for gluing to PVC pipe. Can be used for concrete and pre-fabricated pools. Also available with S.S. AISI 316 drain grille. Connection 2". Max flow rate 12 m<sup>3</sup>/hr, designed for surface suction velocity not exceeding 0.5 m/s.



Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590024	SPA Drain 2" ABS	2.92	0.0098	6
00590027	SPA Drain 2" ABS with S.S. Grille	4.53	0.0098	6



## Adjustable Air Inlet

Controls air to venture system with 1" orifice for air regulation. The knob is mounted on the deck of the SPA tub and is connected to the air venture pipe of the message jet enabling users to regulate the air flow into the message jet.

1" threaded fitting made of white PVC with chrome plated front panel.

Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590047	Adjustable Air Inlet Cr	0.55	0.028	10



## Pneumatic Press Button

Used for starting and ending massage functions. Chrome plated front panel.

Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590045	Pneumatic Press Button	0.52	0.078	10



## Pneumatic Switch

Used with pneumatic press button for starting and ending massage functions.

Code	Description	Weight (kg)	Volume (m <sup>3</sup> )	Std Packing
00590049	Pneumatic Switch	0.53	0.0098	10