

Atecpool EVA LED

Commercial & Sports Lighting

Atecpool EVA A6 & EVA A12 LED Commercial Lighting



Atecpool EVA are high-quality LED solutions for commercial swimming pools and sports facilities, have been used in over 250 public swimming pools and 1000 residential pools around the world. Atecpool EVA LED lighting models demonstrably meet the international safety standard for underwater lighting IEC EN 60598-2-18. All EVA A6 and A12 LED light supply includes mono driver (power box A6 / A12 mono) for fixed colour and RGBW driver (power box A6 / A12 RGBW) for multi colour with a cable length of 10 meters.



EVA A6



EVA A12



Model	EVA A6 Fixed Colour	EVA A12 Fixed Colour	EVA A6 RGBW Multi Colour	EVA A12 RGBW Multi Colour
Code	71770	71790	71780	71793
Type of Light	IP68 LED underwater light			
Max. Energy consumption system	20 W	40 W	20 W Constant Output (10% tolerance) - IPC	40 W Constant Output (10% tolerance) - IPC
Colour Temperatures	Light colour to be determined through connection of wires, options: White, blue, sky blue (light blue), Mediterranean blue (green blue), green, red, purple, magenta, yellow, etc.		Multi-coloured light: • RGBW Red / Green / Blue / Daylight white (6500K) • RGBWW Red / Green / Blue / Warm white (2700K)	
Max. Water Temperature	50°C	40°C	50°C	40°C
Max. Installation depth	25 m			
Diameter	Ø 117 mm			
Depth Luminaire	17 mm			
Cable Length Luminaire	10 m (5x0.5 mm ²)			
Safety Standard Compliance	IEC EN 60598-2-18			
Driver input/output	100-240V AC / 24V DC			
Driving Technology	110V DC (dimming)		DMX 512 (colour mode, scenes, dimming, etc.)	
Protection Rating power box	IP65	IP65	IP65	IP65
Protections power supply	Short circuit, overload, overvoltage, SELV equiv., Class 2 output, double insulation.			
Max. cable length	100m. (7x4 mm ²)		100m. (7x4 mm ²)	
Working temperature	-20°C to +40°C			
Light output at 6500K	Comparable to 200 W Halogen	Comparable to 400 W Halogen	Comparable to 200 W Halogen	Comparable to 400 W Halogen



Easy Colour Picker



Multi-angle light beam



International Safety Tested IEC EN 60598-2-18



Fast Return on Investment




No loss of LED capacity in RGBW



2 years warranty

Light distribution curve A6 6500K white



Light distribution curve A12 6500K white

